

How To Use The AccuArt™ Family of Inkjet Media Products

INSTRUCTIONS FOR USING



1. Prepare artwork for output. Remember, the quality of your digital artwork will determine the quality of your positive/negative. Artwork should have smooth lines and edges and be of adequate resolution.

A minimum of 720 dpi is recommended (1440 dpi or higher for line art).

2. Load the film into the printer. It is important to load the printer so that the coated side of the film will be face-up under the print head. Most printers require the film to be loaded coated side down in the printer tray. As the film is fed through the printer, the coated side will face upward to receive the ink. If your printer loads from the back or if you are using rolls, the film should be loaded with the coated side facing up. To assist in determining the proper print side, the coated print side of the film has a slightly duller appearance.

3. Check printer settings. Make sure printer is set for the highest resolution and print quality. Note that the higher the resolution, the slower the print. Next, set the Media Setting to Photo Quality Glossy Film (if an option, otherwise choose similar film or transparency setting). Options will vary based on printer and software available. Then, set ink deposit for optimum results.

TIP: Experiment with the setting options available with your printer to determine the best set-up for your requirements. If positive seems light or lacks density, try increasing the print quality or amount of ink deposit.



4. Print. These inkjet films dry quickly. With most inks, the positive will be dry and ready for use in less than 2 minutes. AccuMark films are not waterproof and may take longer to dry, especially in areas with high humidity. Drying times will vary based on printers, inks and conditions. Note: Always make sure positive is completely dry before using. Transfer or marring of image can occur if used before completely dry. Refer to product selection chart for ink type.

PLEASE NOTE: AccuArt 3, AccuArt 2, AccuBlack, AccuMark and AccuFast inkjet films are designed to work with standard inkjet printers. Results will vary based on printer used, type of ink, software and artwork quality. Generally, printers with higher resolution capability will yield better looking positives. But remember, image quality depends the most on having quality artwork with adequate resolution and smooth line edges. As with any digital media, experimentation is necessary to determine the proper equipment settings to achieve desired results.

5. Storage. Positives/negatives created with AccuArt inkjet products are re-usable and can be stored for later use. For best results, interleaf positives with a clean piece of newsprint and store in a low humidity environment.

Product Selection Chart

Product Name	Waterproof	Density	Clarity	Halftones	Color Printing	Ink Type
AccuArt 3	Yes	DMAX up to 4.0	DMIN .10	Up to 65 lpi	Yes	Dye, Pigment or K3
AccuArt 2	Yes	DMAX up to 4.6	DMIN .13	Up to 65 lpi	Yes	Dye or Pigment
AccuBlack	Yes	DMAX up to 4.0	DMIN .07	Up to 65 lpi	No	Dye
AccuMark	No	DMAX up to 3.0	DMIN .045	Up to 65 lpi	Yes	Dye
AccuFast	Yes	DMAX up to 4.6	DMIN .13	Up to 65 lpi	Yes	Dye, Pigment or K3

For additional information or technical assistance, contact:

For Screen Printing Questions
Chromaline Screen Print Products
 Toll Free: 800-328-4261
 sales@chromaline.com
 www.chromaline.com

For Sandcarving Questions
Ikonics Imaging
 Toll Free: 800-643-1037
 info@ikonicsimaging.com
 www.ikonicsimaging.com